



## AGL 65 AL

### Extreme pressure grease for accidental contact with foodstuffs

#### Description

Low-viscosity mineral oil, complex aluminium thickener. Resistant to water. Temperature resistance. Excellent, excellent stability to impact and vibrations. Resistant to corrosion and oxidation. High-performance anti-wear and extreme pressure. AGL 65 AL is registered by NSF International, in category H1. This indicates that it is authorized for use in incidental contact with food. (N° 147547)

#### Applications

Bearing lubrication, axles operating under severe conditions in the food industry: load, moisture, high temperature. Can be used in centralised lubrication. For the pelleting/animal feed industries. Food and sugar industries.

#### Technical data

Operating temperature range: -20°C to +140°C

NLGI Grade: 2

Load: 400 kg

Reference	designation	Packaging				food certificate number
AGL65AL50	GREASE- NLGI2-FOOD GRADE-AGL 65 AL-KEG 50KG	TONNELET		KEG	50 KG	147547
AGL65ALCA	GREASE- NLGI2-FOOD GRADE-AGL 65 AL-CARTRIDGE 400GR	CARTON	24	CARTRIDGE	400 G	147547
AGL65ALFT	GREASE- NLGI2-FOOD GRADE-AGL 65 AL-DRUM 180KG- WITH POUCH	FUT		DRUM	180 KG	147547